



2025 Street Stock Rules

(03-07-2025)

BASE WEIGHT

- a) The minimum weight before qualifying or any race is 3100 pounds including the driver. Minimum right-side weight of 1,333 pounds. All weights pre-race, race ready.
- b) Add 100 pounds for non-stock appearing body. No Outlaw Late Model style bodies of Next Generation template bodies.
- c) Add 50 pounds to passenger side front corner for engine set back more than 2", with a maximum of 4" set back.

TIRES

- a) Hoosier 890 tires will be used in the Street Stock division.
- b) **Tire soaking and/or any other types of tire tampering is prohibited.**
- c) **Tires are required to have baby powder inside.**
- d) Steel 8" racing safety wheels with 1" lug nuts.
- e) Track width will be 75" measured at wheel outer bead.

FRAME

- a) The minimum wheelbase is **108"**. Wheelbase 105"-107" allowed with 100# additional weight (3,200 #)
- b) Rear wheel drive, stock OEM clip frames only.
- c) Frame must utilize stock factory produced front cross members, stock factory produced side rails, stock factory produced rear cross member. (factory produced means "original equipment manufacturer produced, not aftermarket)
- d) Wheelbase may be altered from factory length to no shorter than 105"
- e) No tubular fabricated chassis of anykind.
- f) Minimum fuel cell height off the ground will be 8" which can be checked before qualifying or any race.
- g) Stock OEM style gearbox; no rack and pinion steering components allowed.
- h) Factory suspension mounts must be retained other than the upper A-frame mounts on the front clip. Factory mounts are to be within + or - 1" of the O.E.M. configuration.
- i) Tubular frame structure is allowed from the centerline of axle rearward to reinforce the fuel cell to bumper area. 2"x3".095 WALL minimum. This is the only tube frame modification allowed.
- j) Cars must be able to cross over scales without dragging.



2025 Street Stock Rules

(03-07-2025)

BODY

- a) OEM style stock appearing body from front to rear. No flat sides or stretched out bodies. ABSOLUTELY NO OUTLAW FABRICATED TYPE BODIES. NO EXCEPTIONS.
- b) All cars will have an unaltered Five Star equivalent nose and tail piece. There will be no gaps or overlapped panels that will let air escape. Mount these panels as they were intended to be mounted. All nose and tail pieces will be mounted in a stock fashion. The same thing goes for the material joining fenders to the nose piece. A aftermarket Camaro nose piece can be run on a full stock bodied Camaro. No homemade rear tail panels or nose pieces. Cars incorporating a stock type header panel or look are the exception to this rule. A 59 Pontiac can still look like a 59 Pontiac. A 67 Mustang can still look like a 67 Mustang. A 1969 Camaro can look like a 1969 Camaro. Vintage steel original bodies are encouraged.
- c) All cars with stock appearing bodies will be allowed a **6" x 60"** flat clear spoiler centered – **1" lip facing rear allowed.**
- d) All truck bodies require a back window, a flat tonneau cover up to the top of the bed and have minimal rake on the bed. No downforce designed truck beds.
- e) All Street Stocks will retain windshield posts which will be steel or fiberglass. No wraparound windshields of any kind. No stretching the pillars out to achieve more roof or windshield angle. Roof and windshield angles are to remain close to OEM measurements.
- f) No mixing and matching of car bodies from front to rear. (no car body noses and truck rears, etc.)
- g) Rear quarter panels must remain relatively close to that of stock body measurements. No manipulation of the right-side quarter panel shelf. right and left quarter panels must be symmetrical at c pillar.
- h) No cars or trucks will have any extra rake built into their bodies from front to rear.
- i) No body panel or nose piece will be lower than 5" off the ground (measured with driver in the car).
- j) Rub rails are allowed with no sharp edges or fasteners.
- k) A Lexan windshield is mandatory.



2025 Street Stock Rules

(03-07-2025)

SHOCKS AND SUSPENSION

- a) No bump stops of any kind.
- b) Rear trailing arms can be OEM or manufactured. Adjustable heims are permissible; however, the frame mounts and the rear end mounts will remain stock and in stock location. All trailing arm lengths must be within 1" of a stock OEM trailing arm for that car.
- c) All remaining suspension parts will remain stock, be in the stock location and be mounted in the stock angle with the exception of the front shocks which can be mounted outboard.
- d) Rear springs and shocks must be stock appearing and in stock location.
- e) Heim ends are allowed only on shock ends, rear trailing arms and in place of front tie rod ends.
- f) Sway bars must remain stock (no splined sway bars) but may be mounted above or below the control arms. Threaded rod adjustments on the A-frame are permissible.
- g) Rear and/or front load bolts (screw jacks) are allowable.
- h) Aftermarket tubular upper A-Frames are allowed. A-frames will have stock type ball joints (no mono-balls). Upper A-Frame mounts may be modified and be within 1" of the stock location.
- i) All shocks will be steel and non-adjustable. No canister shocks of any kind. No bump stops of any kind. No Schrader valves of any kind. All shocks will be a nationally advertised shock and will not exceed a list price of \$165 per shock.
- j) No coil binding.
- k) No three link rear suspensions. No panhard, j-bar, watts linkage, track bar, lift bar/arm or any other suspension allowed other than factory converging 4 link type or leaf spring.
- l) No strut arm type front suspensions.
- m) Tech may remove a shock at any time to inspect for internal bump stops or bump springs.
- n) Front and rear spring pockets may be modified in the stock frame rails and stock cross member for screw jacks. (jack plates, spring height location. must retain factory rear cross member. Height of jack plate may be adjusted. Factory rear spring pockets must remain and in stock location.) A 2"x 4" or equivalent steel brace may be used as additional support or in lieu of weak rear cross member with Race Director approval.



2025 Street Stock Rules

(03-07-2025)

ENGINES/DRIVE TRAIN

- a) Engines must be stock appearing, all cast iron block and heads and in stock location.
- b) Cast iron or aluminum intake.
- c) Cast iron exhausts manifolds or headers are allowed with 3" maximum exhaust tubing.
- d) The carburetor will be a single 2 or 4 barrel with a maximum 1" store bought adapter or spacer.
- e) HEI style ignition or MSD style ignition permissible. No Traction Control Devices allowed.
- f) OEM automatic or standard transmission.
- g) OEM automatic or standard transmission, inexpensive racing transmissions are allowed (Bert, Brinn or Falcon). **No High-Tower or Quick-Shift transmissions. No Reverse-Mount Starters allowed.** If racing transmission other than Powerglide or TH350/400 will ADD 50LBS. Richmond, TEX or any other racing transmissions designed to shift on restarts are not allowed.
- h) Minimum clutch size will be 7¼". A 2" inspection hole must be cut in all bell housings so the clutch can be easily seen.
- i) Stock style OEM rear ends only; four link or leaf suspension only.
- j) Absolutely NO TRACTION CONTROL allowed!
- k) A steel 9" Ford is permissible with 4 link mount or leaf mount.
- l) No quick-change rear ends or aluminum rear end components of any kind.
- m) Full steel spool, steel mini spool or welded rear ends only, no limited slip differentials. Active Gleason Torsen Differentials or equivalents are not allowed.

BRAKES

- a) Aftermarket brake pedals and or master cylinders are allowed.
- b) Aftermarket brake calipers are allowed.
- c) Rear disc brakes are permissible. No in cockpit adjustments of any kind including brake bias adjuster. All pedals will be in a relatively stock location and the driver will be seated relatively in stock location.



2025 Street Stock Rules

(03-07-2025)

COCKPIT

- a) The full floorboard and front firewall may remain stock or be fabricated.
- b) A fabricated foot box must have sides and bottom that are a minimum thickness of 1/8" steel. No thin gauge sheet metal foot boxes will be allowed.
- c) The passenger side sheet metal/floorboard will remain low next to the driver going over to the right side frame rail.
- d) An aftermarket gas pedal is highly recommended.
- e) The main driver's hoop and door bar construction of the roll cage will be 1 3/4" tubing .095 wall thickness minimum. It will have driver's side door plate reinforcement on the door bars welded in place.

FUEL CELL

- a) Fuel cells are mandatory with an 8" minimum ground clearance.
- b) A fuel cell guard behind the cell with two forward braces is required. Any plating of the frame around the fuel cell is permissible.
- c) Stock rear frame rails may be replaced from behind the spring pockets rearward to the bumper with 2" x 3" steel tubing.